


ASAHI AV VALVE AND PIPING SYSTEMS

ASAHI AV VALVES


SWING CHECK VALVE 15mm - 200mm(1/2inch - 8inch)



SWING CHECK VALVE 15mm - 200mm (1/2inch - 8inch)



15mm (1/2inch), 20mm (3/4inch)



25mm (1inch) - 200mm (8inch)

FEATURES


- The SWING CHECK VALVE prevents backflow, thus protecting equipment, such as a pump.
- Being of a swing arm type, the valve gives little resistance to flow.
- The SWING CHECK VALVE is highly resistant to corrosive chemicals, acid and alkaline, because of its plastic construction.
- To maintain the SWING CHECK VALVE, only the bonnet lid has to be removed, without taking the body out of pipeline.

MATERIAL AND WORKING TEMPERATURE RANGES


Body material	Working Temperature °C (°F)	Max. Working Pressure (at R.T.) MPa {kgf/cm²} [PSI]		
		15 (1/2inch) - 80 (3inch)	100 (4inch) - 150 (6inch)	200 (8inch)
HI-PVC	0 - 50 (30 - 120)	1.0 {10.2} [150]	0.7 {7.1} [100]	0.5 {5.1} [70]
PP	-20 - 80 (-5 - 175)	1.0 {10.2} [150]	0.7 {7.1} [100]	0.5 {5.1} [70]
PVDF	-20 - 100 (-5 - 210)	1.0 {10.2} [150]	0.7 {7.1} [100]	0.5 {5.1} [70]

PARTS & MATERIALS O-ring Type


● 15mm (1/2inch) · 20mm (3/4inch)



● 25mm (1inch) - 200mm (8inch)



X-X



● PP

No.	DESCRIPTION	Pcs.	MATERIAL	REMARKS
①	BODY	1	PP	
②	BONNET	1	PP	
③	SHAFT	1	PP	
④	PLUG	1	PP	
⑤	5a DISC	1	PVDF	
	5b SEAT HOLDER	1	PP	
	5c BOLT(A)	—	PP	Used for Size 25~200mm
	5d ARM	1	PP	Used for Size 25~200mm
	5e WASHER	1	PP	Used for Size 25~200mm
	5f NUT(A)	1	PVDF	Used for Size 25~200mm
	5g PIN	1	PVDF	In Case Material is PVDF, Used for Size 65~200mm
	5h BOLT(B)	1	PP	Used for Size 15,20mm
	5i NUT(B)	1	PP	Used for Size 15,20mm
	5j SEAT	1	GASKET, SEAT, O-RING(A)/O-RING(B)	Used for Size 15,20mm
5k O-RING(A)	1			
⑦	GASKET(B)	1	EPDM/EPDM Others/Others	
⑧	O-RING(B)	1	PTFE/FKM-F PTFE/FKM-C	
⑨	BOLT·NUT	—	STAINLESS STEEL(SUS304)	Used for Size 25~200mm
1a	BODY RING	—	STAINLESS STEEL(SUS304)	Used for Size 15,20mm




Note: 1) 1a Body-ring is available for PP Body 15mm (1/2inch) · 20mm (3/4inch).

● HI-PVC, PVDF

No.	DESCRIPTION	Pcs.	MATERIAL	REMARKS
①	BODY	1	HI-PVC, PVDF	
②	BONNET	1	HI-PVC, PVDF	
③	SHAFT	1	HI-PVC, PVDF	
④	PLUG	1	HI-PVC, PVDF	
⑤	5a DISC	1	HI-PVC, PVDF	
	5b SEAT HOLDER	1	HI-PVC, PVDF	
	5c BOLT(A)	—	HI-PVC, PVDF	Used for Size 25~200mm
	5d ARM	1	HI-PVC, PVDF	Used for Size 25~200mm
	5e WASHER	1	HI-PVC, PVDF	Used for Size 25~200mm
	5f NUT(A)	1	HI-PVC, PVDF	Used for Size 25~200mm
	5g PIN	1	HI-PVC, PVDF	In Case Material is PVDF, Used for Size 65~200mm
	5h BOLT(B)	1	HI-PVC, PVDF	Used for Size 15,20mm
	5i NUT(B)	1	HI-PVC, PVDF	Used for Size 15,20mm
	5j SEAT	1	GASKET, SEAT, O-RING(A)/O-RING(B)	Used for Size 15,20mm
5k O-RING(A)	1			
⑦	GASKET(B)	1	EPDM/EPDM Others/Others PTFE/PFA※	※FKM Covered at PFA
⑧	O-RING(B)	1	PTFE/FKM-F PTFE/FKM-C	
⑨	BOLT·NUT	—	STAINLESS STEEL(SUS304)	Used for Size 25~200mm

WORKING PRESSURE VS. TEMPERATURE

SWING CHECK VALVE O-ring Type



DIMENSIONS TABLE

DIN		Unit:mm										
Nominal Size		d	DIN PN10				D ₁	L	t			H
mm	inch		D	C	n	h			HI-PVC	PP	PVDF	
15	1/2	20	95	65	4	14	86	140	15	15	15	87
20	3/4	20	105	75	4	14	86	140	15	15	15	87
25	1	25	115	85	4	14	130	160	16	16	16	117
32	1 1/4	40	140	100	4	18	145	180	18	17	18	135
40	1 1/2	40	150	110	4	18	145	180	18	17	18	135
50	2	50	165	125	4	18	180	200	20	20	21	161
65	2 1/2	65	185	145	4	18	200	240	22	22	23	165
80	3	80	200	160	8	18	205	260	22	22	23	168
100	4	100	220	180	8	18	265	300	24	24	26	210
125	5	125	250	210	8	18	330	350	24	25	26	245
150	6	150	285	240	8	22	370	400	25	26	27	280
200	8	200	340	295	8	22	425	500	30	31	33	333

ANSI		Unit:inch										
Nominal Size		d	ANSI CLASS 150				D ₁	L	t			H
inch	mm		D	C	n	h			HI-PVC	PP	PVDF	
1/2	15	0.79	3.50	2.38	4	0.62	3.39	5.51	0.59	0.59	0.59	3.43
3/4	20	0.79	3.88	2.75	4	0.62	3.39	5.51	0.59	0.59	0.59	3.43
1	25	0.98	4.25	3.12	4	0.62	5.12	6.30	0.63	0.63	0.63	4.61
1 1/4	32	—	—	—	—	—	—	—	—	—	—	—
1 1/2	40	1.57	5.00	3.88	4	0.62	5.71	7.09	0.71	0.67	0.71	5.32
2	50	1.97	6.00	4.75	4	0.75	7.09	7.87	0.79	0.79	0.83	6.34
2 1/2	65	2.56	7.00	5.50	4	0.75	7.87	9.45	0.87	0.87	0.91	6.50
3	80	3.15	7.50	6.00	4	0.75	8.07	10.24	0.87	0.87	0.91	6.62
4	100	3.94	9.00	7.50	8	0.75	10.43	11.81	0.94	0.94	1.02	8.27
5	125	4.92	10.00	8.50	8	0.88	12.99	13.78	0.94	0.98	1.02	9.65
6	150	5.91	11.00	9.50	8	0.88	14.57	15.75	0.98	1.02	1.06	11.03
8	200	7.87	13.50	11.75	8	0.88	16.73	19.69	1.18	1.22	1.30	13.11

* Important: The swing check valve can be used in both vertical and horizontal pipelines. However, when installing the valve, be sure to make the direction of the arrow embossed on the valve agree with that of flow.

* Swing check valves 15mm(1/2inch) and 30mm(1 1/4inch) mm in nominal size are made out of those in 20mm(3/4inch) and 40mm(1 1/2inch) in nominal size, respectively.

Note : For pressure limits by fluid temperature ranges and materials, see "WORKING PRESSURE VS. TEMPERATURE" in this catalog.



AURO LOCATIONS

AURO Armaturen- und RohrhandelsgesmbH
Lichtblaustraße 21
A-1220 Wien
Austria
Tel: +43/1/2565555
Fax: +43/1/25655555
E-Mail: wien@auro.cc

AURO Bulgaria EOOD
Illianci
3, Azalia Str.
BG-Sofia 1271
Bulgaria
Tel: +359/2/4894519
Fax: +359/2/4894722
E-Mail: bulgaria@auro.cc

AURO spol s.r.o
Technická 2/539
CZ-66448 Moravany u Brna
Czech Republic
Tel: +420/54/5233328
Fax: +420/54/5234753
E-Mail: auro@auro.cz

SC AURO Romania SRL
25-27, Celofibrei Str.
RO-077025 Bragadiru
Judetul Ilfov
Romania
Tel: +40/21/4205217
Fax: +40/21/4205218
E-Mail: romania@auro.cc

AURO Budapest Kft.
Gyár u. 2
H-2040 Budaörs
Hungaria
Tel: +36/23/503920
Fax: +36/23/503921
E-Mail: aurobp@aurobp.hu